

Center Hole

CYLINDERS RT SERIES

17½-100 Ton
Single- Acting,
Spring-Return &
Double-Acting

Ideal for pulling and pressing.

CYLINDERS



RT 302

- A proven design; used throughout industry for over 40 years.
- Cylinders withstand full "dead-end" loads.
- Compact design; ideal for applications in which space is limited.
- Basic head can be changed from a tapped hole to plain hole by simply changing insert.
- Pistons have "Power Tech" treatment for corrosion and abrasion resistance.




"QUICK CHANGE" HEAD INSERTS FOR RT SERIES CYLINDERS

For Use With:	Threaded Order No.*	Plain Order No.
RT172	21669	21714
RT302	21873	21872
RT503	22274	22275
RT1004	24197	24196

* Provided with cylinder

Switch from a tapped hole to a plain hole quickly with these cylinder head inserts. They are held in place with a socket screw. Plain hole permits use of a speed nut for readjusting cylinder after extension.

Dimensions for reference only.




Cyl. Capacity (Tons)	Stroke (mm)	Order No.	Oil Cap. (cm³)	A Re-tracted Height (mm)	B Ex-tended Height (mm)	C1 Out-tended height (mm)	C2 Out-side Dia. (mm)	L Load Cap Dia. (mm)	M Load Cap Dia. (in.)	N Center Hole Dia. (mm)	Z Mounting Location (mm)	Cyl. Mounting Hole Area (cm²)	Metric Tons at 700 bar	Weight (kg)	
17,5	50,8	RT172	116	-	174,6	225,4	95,3	146,1	44,5	1-8	27,0	38,1	8,7	22,8	16,1 6,6
30	63,5	RT302	258	-	214,3	277,8	108,0	190,5	57,2	1 1/4-7	32,9	46,0	11,9	40,5	28,5 12,8
50	76,2	RT503	482	-	268,3	344,5	149,2	238,1	73,0	1 5/8-5 1/2	42,5	60,3	16,7	63,3	44,5 25,4
100	123,8	RT1004** 1.5831.037	384,2	508,0	266,7	336,6	120,7	2 1/2-8	65,1	73,0	19,8	124,1*	87,3	72,6	

* Push side only for RT1004 double-acting cylinder.

** The RT1004 has a bypass when full stroke is reached, preventing over-pressurization of the cylinder.

NOTE: Each cylinder complete with threaded cylinder head insert, cylinder half coupler and cylinder attaching screws.



"CENTER-HOLE" CYLINDER ACCESSORIES (OPTIONAL)

RT172, RH203	RT302, RH302 RH303, RH306	RT503, RH503, RH603 RH605, RH606	RT1004
RHA20	RHA30	RHA50	RHA100
1 Speed Crank	27198	29595	303785
2 Speed Nut	302482	33439	34136
3 Adjusting Screw	32118	34758	32699
4 Threaded Insert	Order threaded insert for RH series cylinders with the accessory set. (See above) Threaded insert supplied with RT series cylinders.		
5 Pushing Adapter	201923	34510	34755
	1"-8, 12,7 mm dia. shank	1 1/4"-7 x 19,1mm dia. shank	1 5/8"-5 1/2" x 25,4 mm dia. shank
6 Pushing Adapter	201454	34511	34756
	1"-8, 19,5 mm dia. shank	1 1/4"-7 x 25,4 mm dia. shank	1 5/8"-5 1/2" x 31,7 mm dia. shank
7 Jack Screw	24813	25931	32701
	1"-8 x 177,8 mm Lg.	1 1/4"-7 x 228,6 mm Lg.	1 5/8"-5 1/2" x 279,4 mm Lg.
8 Screw Cap	28228	28229	28230
	1"-8 x 38,1 mm dia.	1 1/4"-7 x 44,4 mm dia	1 5/8"-5 1/2" x 571,5 mm Lg.